



ITEM NO.型號	HOUR CONTER 累時器				COUNTER 計數器			
	LHS-6	LHS-8	LHS-6V	LHS-8V	LCS-6	LCS-8	LCS-6V	LCS-8V
COUNT INPUT 信號輸入	●Contact Input: By short circuit 將接點 1-2 短路 ●Maximum short-circuit impedance 短路時最大阻抗≤10KΩ ON Minimum open impedance 開路時最小阻抗≥500KΩ OFF		●Voltage Input: 24-240V AC/DC or 3-36VDC 電壓輸入：在接點 1-2 輸入 24-240V 交直流通用 或者 3-36V 直流		●Contact Input: By short circuit 將接點 1-2 短路 ●Maximum short-circuit impedance 短路時最大阻抗≤10KΩ ON Minimum open impedance 開路時最小阻抗≥500KΩ OFF		●Voltage Input: 24-240V AC/DC or 3-36VDC 電壓輸入：在接點 1-2 輸入 24-240V 交直流通用 或者 3-36V 直流	
NUMBER OF COUNTS 計數範圍	9999H59M	999999H59M	9999H59M	999999H59M	0-999999	0-99999999	0-999999	0-99999999
COUNTING SPEED 累時 (計數) 速率	SIGNAL WIDTH:≥1SEC				10 CPS (SIGNAL WIDTH: 50ms)			
	接點 1-2 短路≥1 秒		接點 1-2 輸入電壓信號≥1 秒		每秒 10 次			
RESET 重置輸入	BY SHORT CIRCUIT SIGNAL WIDTH:≥0.2SEC.(將接點 3-4 短路≥0.2 秒)							
CONNECTION DIAGRAM 線路圖								
	COUNT INPUT 累時輸入： 1-2		RESET INPUT 重置輸入： 3-4		COUNT INPUT 計數輸入： 1-2		RESET INPUT 重置輸入： 3-4	